



PD.CD1N

COMPRESSION DRIVER

1.73" / 44 mm
VOICE COIL DIAMETER


900 Hz - 19 kHz
FREQUENCY RESPONSE

109 dB
SENSITIVITY (1W / 1m)


40 W (A.E.S.)
POWER HANDLING

1.0" / 25.4 mm
SOUND CHANNEL / THROAT SIZE

FREQUENCY RESPONSE AND IMPEDANCE CHARTS



Measurement taken on custom horn.



1. AES standard practice with high pass filter set at specified lower limiting frequency for two hours.

2. Sensitivity is measured with applied pink noise RMS Voltage set to 2.83V for nominal 8 ohms impedance and measurement taken at 1 metre from mouth of horn. Average SPL taken between 2000 to 10000 kHz.

3. Frequency range is defined as measured frequency-10dB to rated sensitivity.

FEATURES:

- The PD.CD1N features an annular slot optimised geometry ABS phase plug.
- 44 mm Aluminium voice coil utilising high temperature Kapton former.
- PEEK diaphragm and surround material.
- Neodymium motor structure.

The PD.CD1N is an ideal driver for professional high performance applications that can be used in traditional 2-way systems or as part of a larger multi-way long throw system. The neodymium motor structure allows close coupling due to the compact size and footprint.

Adaptor plate is available for traditional Flare PCD fixings.



GENERAL SPECIFICATIONS

Sound Channel / Throat Size	1.0" / 25.4 mm
Voice Coil Diameter	1.73" / 44 mm
Available Impedances	4 Ohm / 8 Ohm / 16 Ohm
Power Rating (above 1kHz) ¹	40 W (A.E.S.)
Sensitivity (1W - 1m, on axis, on horn) ²	109 dB
Frequency Range ³	900 Hz - 19 kHz
Recommended Crossover Frequency (Filtered at 18 dB/ Octave)	1800 Hz
Minimum Impedance	2.6 kHz - 7.5 Ω
Voice Coil Material	Copper Clad Aluminium
Coil Former Material	Kapton
Flux Density	1.8 Tesla
Diaphragm Material	PEEK
Suspension Material	PEEK
Surround / Edge Termination	Flat
Phase Plug Design	Annular
Phase Plug Material	ABS
Magnet Material	Neodymium
Connector Type	Solder Tab

DIMENSIONS

Overall Diameter	85 mm
Overall Height	41 mm

MOUNTING INFORMATION

Fitting	2 x 6 mm threaded holes
Mounting PCD	76 mm

WEIGHT

Nett Weight	0.85 kg / 1.87 lb
Shipping Weight	1 kg / 2.2 lb